

TORERO

BOLT & NUT SETTERS

Straight shut-off oil-pulse wrench/screwdriver(High pressure tool)



OBT-40SD



OBT-50SD



OBT-60SD



OBT-70SD



OBT-80SD



OBT-81SD



OBT-40SH



OBT-50SH



OBT-60SH



OBT-70SH

Straight high pressure oil-pulse tool (Suit for pressure 0.5-0.6MPa = 72.5 - 87 psi)

Model	Bolt dia.	Torque range	Socket or bit	Free speed			Whole length	Weight	Air inlet	Rec. hose size	Air consumption	Noise level
		Nm		rpm								
	mm	0.5-0.6Mpa	in	0..4Mpa	0.5Mpa	0.6Mpa	mm	kg	in	mm	m3/min	dB(A)
OBT-40SD	5	5-9	3/8	3600	3800	4000	218	0.83	PT 1/4	6.5	0.2	70
OBT-50SD	5-6	7-16	3/8	-	-	5000	218	0.83	PT 1/4	6.5	0.25	78
OBT-60SD	8	20-32	3/8	-	-	6000	228	0.87	PT 1/4	6.5	0.3	80
OBT-70SD	8-10	30-50	3/8	-	-	5800	240.5	0.95	PT 1/4	8.0	0.35	80
OBT-80SD	8-10	42-60	3/8	-	-	6000	246.5	1.2	PT 1/4	8.0	0.48	80
OBT-81SD	10	48-65	1/2	-	-	6000	251.5	1.25	PT 1/4	8.0	0.48	80
OBT-40SH	5	5-9	1/4	3600	3800	4000	220.5	0.83	PT 1/4	6.5	0.2	70
OBT-50SH	5-6	7-16	1/4	-	-	5000	220.5	0.83	PT 1/4	6.5	0.25	78
OBT-60SH	6-8	16-28	1/4	-	-	6000	230.5	0.87	PT 1/4	6.5	0.3	80
OBT-70SH	8	20-32	1/4	-	-	5800	240.5	0.95	PT 1/4	8.0	0.4	80

Note : Oil-pulse tool can reach torque will be slightly different as actual tightening torque. It will depend on condition of working area and joint situation. Testing the selected model in actual condition is advised. Please reference the following :

Hard joint application : 70% of the maximum torque range in the catalogue.

Soft joint application : The minimum of the torque in the catalogue.