

TORERO

CLUTCH SCREWDRIVER

Straight shut-off clutch screwdriver tool

LTR



LTU



Order accessories
Order no. : 37513880030

1/8 to 1/4 adapter

The tool air inlet thread PF 1/8 is G 1/8. You can purchase "1/8 to 1/4 adapter " if you need to turn air inlet to PT 1/4.

Touch trigger clutch tool

Model	Torque range	Socket or bit	Free speed	Whole length	Weight	Air inlet	Rec. hose size	Air consumption	Noise
	Nm	in	rpm	mm	kg	in	mm	m3/min	dB(A)
LTR-12SH-1	0.6-1.6	1/4	1900	195	0.55	PF 1/8	6	0.27	75
LTR-12SH-2	0.4-2.3	1/4	1450	195	0.55	PF 1/8	6	0.27	75
LTR-12SH-3	0.4-3.2	1/4	1000	195	0.55	PF 1/8	6	0.27	75
LTR-12SH-4	0.4-4.2	1/4	750	195	0.55	PF 1/8	6	0.27	75
LTR-12SH-5	0.4-5.0	1/4	450	195	0.55	PF 1/8	6	0.27	75

Safety trigger clutch tool

Model	Torque range	Socket or bit	Free speed	Whole length	Weight	Air inlet	Rec. hose size	Air consumption	Noise
	Nm	in	rpm	mm	kg	in	mm	m3/min	dB(A)
LTU-12SH-1	0.6-1.8	1/4	2200	217	0.6	PF 1/8	6	0.36	75
LTU-12SH-2	0.5-2.5	1/4	1700	217	0.6	PF 1/8	6	0.36	75
LTU-12SH-3	0.4-3.5	1/4	1200	217	0.6	PF 1/8	6	0.36	75
LTU-12SH-4	0.4-4.5	1/4	850	217	0.6	PF 1/8	6	0.36	75