

TORERO

BOLT & NUT SETTERS

Angle shut-off oil-pulse wrench



OBT-50SC



OBT-60SC



OBT-70SC



OBT-80SC

Angle series low pressure oil-pulse tool (Suit for pressure 0.5-0.6MPa = 72.5 - 87 psi)

Model	Bolt dia.	Torque range	Socket or bit	Free speed			Whole length	Weight	Air inlet	Rec. hose size	Air consumption	Noise level
		Nm		rpm								
	mm	0.5-0.6Mpa	in	0..4Mpa	0.5Mpa	0.6Mpa	mm	kg	in	mm	m3/min	dB(A)
OBT-50SC	6-8	7-15	3/8	-	-	4500	258.5	1.35	PT 1/4	6.5	0.25	75
OBT-60SC	8	13-28	3/8	-	-	5200	269.5	1.45	PT 1/4	6.5	0.3	75
OBT-70SC	8	20-35	3/8	-	-	4400	280.5	1.65	PT 1/4	8.0	0.35	78
OBT-80SC	8-10	30-50	1/2	-	-	2500	305.5	1.85	PT 1/4	8.0	0.35	80



OBT-50SCL



OBT-60SCL



OBT-70SCL



OBT-80SCL

Angle high pressure oil-pulse tool (Suit for pressure 0.4-0.5MPa = 58 - 72.5 psi)

Model	Bolt dia.	Torque range	Socket or bit	Free speed			Whole length	Weight	Air inlet	Rec. hose size	Air consumption	Noise level
		Nm		rpm								
	mm	0.4-0.5Mpa	in	0..4Mpa	0.5Mpa	0.6Mpa	mm	kg	in	mm	m3/min	dB(A)
OBT-50SCL	6-8	7-14	3/8	-	4500	-	258.5	1.35	PT 1/4	6.5	0.2	75
OBT-60SCL	8	10-25	3/8	-	5200	-	269.5	1.45	PT 1/4	6.5	0.25	75
OBT-70SCL	8	15-30	3/8	-	4300	-	280.5	1.65	PT 1/4	8.0	0.27	78
OBT-80SCL	8-10	25-45	1/2	-	2300	-	305.5	1.85	PT 1/4	8.0	0.27	80

Note : Oil-pulse tool can reach torque will be slightly different as actual tightening torque. It will depend on condition of working area and joint situation. Testing the selected model in actual condition is advised. Please reference the following :

Hard joint application : 70% of the maximum torque range in the catalogue.

Soft joint application : The minimum of the torque in the catalogue.