

BOLT & NUT SETTERS

Straight non shut-off oil-pulse wrench/screwdriver



OBN-40SD



OBN-50SD



OBN-60SD



OBN-70SD



OBN-80SD



OBN-81SD



OBN-30SH



OBN-40SH



OBN-50SH



OBN-60SH



OBN-70SH

Model	Bolt dia.	Torque range	Socket or bit	Free speed			Whole length	Weight	Air inlet	Rec. hose size	Air consumption	Noise level
		Nm		rpm								
	mm	0.5-0.6Mpa	in	0..4Mpa	0.5Mpa	0.6Mpa	mm	kg	in	mm	m3/min	dB(A)
OBN-40SD	5-6	13-22	3/8	-	-	4000	218	0.62	PT 1/4	6.5	0.23	75
OBN-50SD	6-8	20-35	3/8	-	-	6700	218	0.74	PT 1/4	6.5	0.35	78
OBN-60SD	8-10	32-50	3/8	-	-	6500	228	0.77	PT 1/4	6.5	0.45	80
OBN-70SD	10	40-60	3/8	-	-	6000	240.5	0.87	PT 1/4	8.0	0.45	84
OBN-80SD	10	40-70	3/8	-	-	5800	246.5	1.2	PT 1/4	8.0	0.48	80
OBN-81SD	10-12	50-80	1/2	-	-	5800	251.5	1.25	PT 1/4	8.0	0.48	80
OBN-30SH	5	5-10	1/4	5600	5800	6000	219	0.72	PT 1/4	5.0	0.2	65
OBN-40SH	5-6	11-20	1/4			4000	220.5	0.62	PT 1/4	6.5	0.23	75
OBN-50SH	6-8	18-28	1/4			6700	220.5	0.74	PT 1/4	6.5	0.35	78
OBN-60SH	8	22-35	1/4			6500	230.5	0.77	PT 1/4	6.5	0.45	80
OBN-70SH	8-10	25-40	1/4			6000	240.5	0.87	PT 1/4	8.0	0.45	84

Note : Oil-pulse tool can reach torque will be slightly different as actual tightening torque. It will depend on condition of working area and joint situation. Testing the selected model in actual condition is advised. Please reference the following :

Hard joint application : 70% of the maximum torque range in the catalogue.

Soft joint application : The minimum of the torque in the catalogue.