


D 19 L (AF)

Llave de vaso de 1/2"
Perfil UD de 12 caras,
largo




12,5 1/2"

- > Cuadradillo de accionamiento hembra según DIN 3120 - C 12,5, ISO 1174, con hendidura para bola
- > Para uso manual

Código	N°		L	d1	d2	t	
6141300	D 19L 1/2AF	1/2"	77	18,7	22,5	16,0	0,095
6141490	D 19 L 9/16AF	9/16"	77	20,7	22,5	16,5	0,105
6141570	D 19 L 5/8AF	5/8"	77	22,5	24,0	16,5	0,120
6141650	D 19 L 11/16AF	11/16"	77	24,7	24,8	16,5	0,143
6141730	D 19 L 3/4AF	3/4"	82	26,7	26,0	22,0	0,164
6141810	D 19L 13/16AF	13/16"	82	28,5	28,5	22,0	0,197
6142030	D 19 L 7/8AF	7/8"	82	30,6	28,5	24,0	0,208
6142110	D 19 L 15/16AF	15/16"	82	32,6	29,0	26,0	0,234

TX 19

Llave de vaso de 1/2"
para los tornillos TX
macho





12,5 1/2"

- > Cuadradillo de accionamiento hembra según DIN 3120 - C 12,5, ISO 1174, con hendidura para bola
- > Para uso manual

Código	N°	mm	M	mm	L	d1	d2	t	
6145720	TX 19 E10	E10	M8	9,42	38	13,5	22,5	15,5	0,056
6194180	TX 19 E11	E11	-	10,08	38	14,0	22,5	15,5	0,055
6147340	TX 19 E12	E12	M10	11,17	38	15,5	22,5	15,5	0,059
6147420	TX 19 E14	E14	M12	12,9	38	17,0	22,5	13,0	0,059
6194420	TX 19 E16	E16	M12	14,76	38	19,0	22,5	13,0	0,062
6194500	TX 19 E18	E18	M14	16,7	40	21,0	24,5	14,0	0,078
6194690	TX 19 E20	E20	M16	18,45	40	23,5	24,5	14,0	0,085
6195070	TX 19 E24	E24	M18 - M20	22,16	41,5	28,5	26,0	16,0	0,116

ITX 19

Llave de vaso
destornillador de 1/2"
para los tornillos TX
hembra, cortos





12,5 1/2"

- > Cuadradillo de accionamiento hembra según DIN 3120 - C 12,5, ISO 1174, con hendidura para bola
- > Para uso manual

Código	N°		M	mm	L1	L2	d	
6152930	ITX 19 T20	T20	M4 - M5	3,86	55	17,0	22,5	0,076
6154200	ITX 19 T25	T25	M4,5 - M5	4,43	55	17,0	22,5	0,075
6154630	ITX 19 T27	T27	M4,5 - M6	4,99	55	17,0	22,5	0,076
6156170	ITX 19 T30	T30	M6 - M7	5,52	55	17,0	22,5	0,075
6156330	ITX 19 T40	T40	M7 - M8	6,65	55	17,0	22,5	0,076
6157060	ITX 19 T45	T45	M8 - M10	7,82	55	17,0	22,5	0,077
6158030	ITX 19 T50	T50	M10	8,83	55	17,0	22,5	0,092
6158380	ITX 19 T55	T55	M12	11,22	55	17,0	23	0,107
6158540	ITX 19 T60	T60	M14	13,25	55	15,0	24,7	0,137

ITX 19 L

Llave de vaso destornillador largo de 1/2"
para los tornillos TX
hembra



12,5 1/2"

- > Cuadradillo de accionamiento hembra según DIN 3120 - C 12,5, ISO 1174, con hendidura para bola
- > Para uso manual

Código	N°		M	mm	L1	L2	d	
6188020	ITX 19L T20-100	T20	M4 - M5	3,86	100	62,0	22,5	0,095
6188100	ITX 19L T25-100	T25	M4,5 - M5	4,43	100	62,0	22,5	0,095
6188370	ITX 19L T27-100	T27	M4,5 - M5	4,99	100	62,0	22,5	0,096
6152500	ITX 19L T30-100	T30	M6 - M7	5,52	100	62,0	22,5	0,096
6152690	ITX 19L T40-100	T40	M7 - M8	6,65	100	62,0	22,5	0,096
6155870	ITX 19L T45-100	T45	M8 - M10	7,82	100	62,0	22,5	0,098
6158700	ITX 19L T50-100	T50	M10	8,83	100	62,0	22,5	0,124
6159940	ITX 19L T55-100	T55	M12	11,22	100	62,0	23	0,151
6188450	ITX 19L T60-100	T60	M14	13,25	100	60,0	24,7	0,197
6105180	ITX 19L T70-100	T70	M16	15,55	100	60,0	28	0,277