

TORERO

BOLT & NUT SETTERS

Pistol shut-off oil-pulse wrench/screwdriver(High pressure tool)



OBT-40PD



OBT-50PD



OBT-60PD



OBT-70PD



OBT-80PD



OBT-81PD



OBT-90PD



OBT-100PD



OBT-130PD



OBT-150PD



OBT-180PD



OBT-40PH



OBT-50PH



OBT-60PH



OBT-70PH

Pistol high pressure oil-pulse tool (Suit for pressure 0.5-0.6MPa = 72.5 - 87 psi)

Model	Bolt dia.	Torque range	Socket or bit	Free speed			Whole length	Weight	Air inlet	Rec. hose size	Air con.	Noise level
		Nm		rpm								
	mm	0.5-0.6Mpa	in	0..4 Mpa	0.5 Mpa	0.6 Mpa	mm	kg	in	mm	m3/min	dB(A)
OBT-40PD	5	5-9	3/8	3200	3500	3800	160.5	0.92	PT 1/4	6.5	0.2	75
OBT-50PD	5-6	7-16	3/8	-	-	4800	160.5	0.92	PT 1/4	6.5	0.25	78
OBT-60PD	8	20-32	3/8	-	-	6000	170	0.95	PT 1/4	6.5	0.35	80
OBT-70PD	8-10	30-50	3/8	-	-	5800	183	1.05	PT 1/4	8.0	0.4	80
OBT-80PD	8-10	42-60	3/8	-	-	6000	187	1.25	PT 1/4	8.0	0.48	80
OBT-81PD	10	50-65	1/2	-	-	6000	192	1.25	PT 1/4	8.0	0.48	80
OBT-90PD	10-12	55-85	1/2	-	-	4800	192	1.45	PT 1/4	8.0	0.53	82
OBT-100PD	12	75-115	1/2	-	-	4500	198	1.7	PT 1/4	8.0	0.55	82
OBT-130PD	12-14	90-145	1/2	-	-	3800	215	2.3	PT 1/4	12.7	0.7	82
OBT-150PD	14-16	130-205	3/4	-	-	3400	243.5	2.9	PT 1/4	12.7	0.7	82
OBT-180PD	16-18	170-245	3/4	-	-	3200	262	3.7	PT 3/8	12.7	0.7	82
OBT-40PH	5	5-9	1/4	3200	3500	3800	161	0.92	PT 1/4	6.5	0.2	75
OBT-50PH	5-6	7-16	1/4	-	-	4800	161	0.92	PT 1/4	6.5	0.25	78
OBT-60PH	6-8	16-28	1/4	-	-	6000	171	0.95	PT 1/4	6.5	0.35	80
OBT-70PH	8	20-32	1/4	-	-	5800	183	1.05	PT 1/4	8.0	0.4	80

Note : Oil-pulse tool can reach torque will be slightly different as actual tightening torque. It will depend on condition of working area and joint situation. Testing the selected model in actual condition is advised. Please reference the following :

Hard joint application : 70% of the maximum torque range in the catalogue.

Soft joint application : The minimum of the torque in the catalogue.